

RACK-PROTECTOR-EURO-X12-1U-PI

SPD - for low voltage / SPD type 3 / For RACK 19"


Multi socket outlet with surge protection SPD Type 3 for 19" RACK

visual fault signalling, 3 m power supply cord, industrial plug 16A 2P+PE


- multiple socket outlet with integrated surge protection SPD Type 3
- for 19" RACK
- for protection of information technology equipments against surge voltage
- mounting height 1U
- 12x EURO socket outlet



Product dimensions



Basic circuit diagram



Parameter name			Parameter value
Type of SPD			T3
Mounting			19" rack
Nominal voltage	U_n		230 V AC
Maximum operating voltage	U_c		275.00 V AC
Nominal load current	I_L		16.000 A
Type of network			TN
Maximum overcurrent protection			16 A gL/gG or C 16 A
Short-circuit current rating	I_{SCCR}		6.0 kA
Residual current	I_{PE}		0.004 mA
Nominal discharge current (8/20 μ s) L-N	I_n		3.00 kA
Nominal discharge current (8/20 μ s) L+N-PE	I_n		5.00 kA
Nominal discharge current (8/20 μ s) N-PE	I_n		3.00 kA
Test voltage L-N	U_{oc}		6.0 kV
Test voltage N-PE	U_{oc}		6.0 kV
Test voltage L+N-PE	U_{oc}		10.0 kV
Voltage protection level mode L-N	U_p		1.20 kV
Voltage protection level mode L-PE	U_p		1.50 kV

Voltage protection level mode N-PE	U_p	1.50 kV
Response time L-N	t_a	25 ns
Response time N-PE	t_a	100 ns
Fault indication		red indicator
Degree of protection		IP 20
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000942
Customs tariff number		85363010
EAN		8595090562566
Order number		A06256

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu
 Technická podpora: 800 818 818 | podpora@saltek.cz

05.02.2026 -
23:08:18