

DL-VDSL3

SPD - for data, signalling and telecommunications lines / ICT /

Telecommunications


Two-stage surge protection for high-speed ADSL2

surge protection for high-speed ADSL2, VDSL2, VDSL2+, VDSL3 lines


- two- stage surge protection of high-speed lines ADSL2, VDSL2, VDSL2 +, VDSL3
- installation at boundary LPZ 0 - 1 and higher
- connection of metallic pair via screw terminals
- working voltage up to 60 V DC



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2,C3
Location of SPD		ST 1+2+3
Mounting		DIN rail 35 mm
Maximum operating voltage	U_c	60.00 V DC
Serial resistance per core	R	2.20 Ω
Nominal load current	I_L	0.600 A
C2 nominal discharge current (8/20 μ s) core-core	I_n	5.00 kA
D1 total discharge current (10/350 μ s) cores-PE	I_{Total}	5.00 kA
C2 voltage protection level mode core-core (@ U_{oc}/I_n)	U_p	450,00 V (10 kV / 5 kA)
C2 voltage protection level mode core-PE (@ U_{oc}/I_n)	U_p	1100,00 V (10 kV / 5 kA)
C3 voltage protection level mode core-core (@ I_n - 1 kV/ μ s)	U_p	90,00 V (10 A)
C3 voltage protection level mode core-PE (@ I_n - 1 kV/ μ s)	U_p	600,00 V (10 A)

Response time core-core	t_a	1 ns
Response time core-PE	t_a	100 ns
Treshold frequency core-core	f	300 MHz (@ -1 dB)
Insertion loss	A	<0,2 dB (@ 35 MHz)
Connection (input - output)		terminals-terminals
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 70 °C
Humidity		5 - 95 %
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC000943
Customs tariff number		85363010
EAN		8595090571209
Order number		A07120

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

05.02.2026 -
23:08:08