

FX-090-F75-F/F

SPD - for data, signalling and telecommunications lines / Coaxial lines / ST1 (FX)


Lightning current arrester for common coaxial lines of receivers

F Connectors 75 Ω


- lightning current arrester with grounded shielding
- installation at the boundary of LPZ 0 and LPZ 1 zones at the line entry into building
- for protection of coaxial lines of TV/SAT receivers and CCTV systems, suitable as the 1st level of surge protection in coordination with the SX type
- suitable for DC power distribution
- lower U_p (core-PE)



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2
Location of SPD		ST 1
Mounting		DIN rail 35 mm
Maximum operating voltage	U_c	70.00 V DC
Nominal load current	I_L	4.000 A
Frequency range	f	0,00 - 2300,00 MHz
Impedance	Z	75 Ω
Insertion loss		0.60 dB
VSWR typ. (max.)	VSWR	1,2 (1,5)
D1 impulse discharge current (10/350 μ s) core-PE	I_{imp}	2.50 kA
C2 nominal discharge current (8/20 μ s) core-PE	I_n	10.00 kA
C3 voltage protection level mode core-PE at 1 kV/ μ s	U_p	1 200 V
Response time core-PE	t_a	100 ns

Connection (input - output)	F 75
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class	EC001466
Customs tariff number	85363010
EAN	8595090542124
Order number	A04212

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

06.02.2026 -
02:27:32